



ATLANTIC FULLY SYNTHETIC CVT FLUID

(Full Synthetic CVT Fluid)

DESCRIPTION

ATLANTIC FULLY SYNTHETIC CVT FLUID is a full synthetic lubricant based on carefully selected very high quality base oils that has been designed to be used in most CVT gearboxes. It is suitable for continuously variable transmissions, using steel push-belts or chains. It offers outstanding anti-wear protection and stable friction characteristics.

APPLICATIONS

ATLANTIC FULLY SYNTHETIC CVT FLUID is formulated by carefully balancing base oils and advanced additives, to meet the requirements of both European and Japanese CVT manufacturers. This product may not be used in some hybrid vehicles, requiring special fluids.

PROPERTIES

ATLANTIC FULLY SYNTHETIC CVT FLUID provides outstanding metal-to-metal frictional properties and excellent protection and performance for CVTs throughout vehicle manufacturer-recommended drain intervals. It is Warranty Secure and will not void your vehicle's warranty. ATLANTIC FULLY SYNTHETIC CVT FLUID is a cost-effective, high-performance alternative to original equipment manufacturer (OEM) fluids.

PRODUCT BENEFITS

- Excellent Frictional Properties
- Outstanding Wear Protection
- Resists Heat
- Superior Wet-Clutch Performance
- Help prevent belt and chain slipping and help extend transmission life.
- Effectively resists wear to the transmission's vital parts, helping achieve long life.
- Superior wet-clutch performance for outstanding anti-shudder durability
- Excellent thermal and oxidation stability.
- Extended oil life

RECOMMENDATIONS / SPECIFICATIONS

AUDI TL 52180, DAIHATSU AMIX CVTF DFE, CVTF-DC, FORD WSS -M2C928-A, CVT23, CVT30, MERCON C, GM SATURN DEX-CVT, HONDA HCF -2, HMMF, HYUNDAI SP -CVT1, SP -III, KIA SP -III, MB 236.20, MINI EZL799A, MITSUBISHI CVTF -J1/SP -III, CVTF J-4, NISSAN NS-1/NS-2/NS-3, SUBARU CVT, Lineartronic CVTF, i-CVT, SUZUKI CVTF GREEN 2, TC /NS -2/CVT Green 1, TOYOTA TC, CVT FE, VW G 052 180, G 052 516, BMW 8322 0 136 376, 8322 0 429 154, DODGE/JEEP NS-2, CVTF+4®, MOPAR® CVT 4, ZF CVT V1

Meets or exceeds the quality requirements of most American, Japanese and European manufacturers.

TYPICAL TECHNICAL PROPERTIES

Product code	12710AT
Color, VISUAL	RED
Density at 15 ^o C, g/ml, ASTM D4052	0.852
Kinematic Viscosity at 40 ^o C, mm ² /s, ASTM D445	34.2
Kinematic Viscosity at 100 ^o C, mm ² /s, ASTM D445	7.35
Viscosity Index, ASTM D2270	189
Flash Point(COC), °C, ASTM D92	212
Pour Point, °C, ASTM D97	-45
Brookfield viscosity at -40°C, mPa.s, ASTM D2983	16000

Note: These characteristics are typical of current production. While future production will conform to ATLANTIC's specification, variations in these characteristics may occur.

ATL/ATF/001/0*, 10.07.22, Page 1/1
* supersedes all previous versions

Health and Safety: Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing off used product, take care to protect the environment.