



Mechanic's Choice 15W-40 Engine Oil

Mechanic's Choice 15W-40 Engine Oil is a high quality mineral based multigrade motor oils developed to meet the demanding requirements of the engine manufacturers, protecting your engine from start-up to shutdown. Formulated with a combination of mineral base stocks and the select additive system, ensuring enhanced performance and protection.

Specifications and Approvals

Mechanic's Choice Engine Oil*

SAE 15W-40

API SL

API CF

*Check owners' manual before use.

Applications

Mechanic's Choice 15W-40 can be used in a range of passenger petrol cars where a API SL 15W-40 grade has been recommended.

Also, suitable for diesel vehicles where API CF is recommended. Please consult the owner's manual before use.

Features and Benefits

Superior Protection

Fights the three major causes of engine stress – heat, deposits and wear from Start-up to Shutdown

Viscosity Control

Delivers enhanced durability and lower oil consumption.

Cold start properties

Low temperature viscosity results in easy cold start.

Wear protection

Excellent wear protection and enhances engine life.

PRODUCT INFORMATION



Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit www.valvoline.com.au or contact the Technical Hotline on 1800 804 658 for product recommendations.

Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Mechanic's Choice Engine Oil	Typical
SAE Viscosity Grade	15W-40
Viscosity @ 100 °C, mm ² /s, ASTM D445	14.10
Viscosity @ 40 °C, mm ² /s, ASTM D445	102.6
Viscosity Index, ASTM D2270	140
Density @ 15 °C, kg/L, ASTM D4052	0.8680
Total Base Number, mg KOH/g, ASTM S5293	6.9
CCS Viscosity, mPa.s @ -20 °C, ASTM D5293	5300
Flash Point (COC), °C, ASTM D92	238
Pour Point, °C, ASTM D5950	-36

Note: Mechanic's Choice SAE 15W-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1286.20	20L
1286.28	208L

Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website www.valvoline.com.au

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

Author:

VP - Effective 02-09-2021
Replaces - 1286/04