

## Valvoline Professional Series (VPS) SAE 10W-40

Valvoline Professional Series (VPS) SAE 10W-40 engine oil is designed and formulated exclusively for workshops to meet or exceed the latest specifications from leading vehicle manufacturers. Valvoline Professional Series (VPS) SAE 10W-40 is a specific synthetic blend multigrade engine oil developed to meet the demanding requirements of the engine manufacturers, protecting your engine from start-up to shut down.

Valvoline Professional Series (VPS) SAE 10W-40 engine oil is formulated with a combination of synthetic and mineral base stocks and the most advanced additive system available, ensuring the enhanced performance and protection whilst exceeding many of the toughest requirements of the world's leading manufacturers.

### Specifications and Approvals

Valvoline Professional Series*
SAE 10W-40
API SP, SN, SM
ACEA A3/B4
MB 229.1
VW 501.01, 502.00, 505.00

\*Check owners' manual before use.

### Applications

Valvoline Professional Series SAE 10W-40 synthetic blend motor oils focus to enhance engine durability and fuel efficiency, while maintaining longer drain intervals found in today's passenger cars. Suitable for use in older passenger vehicles with diesel engines where API CF specification oil is recommended.

Please always consult the vehicle owners' manual before use.

### Features and Benefits

#### **Professional Series Product Range**

Synthetic Blend Workshop specific engine oil range to cover modern vehicles

#### **Superior Protection**

VPS engine oil fights the major causes of engine stress, heat, deposits and wear from Start-up to Shut down.

#### **Advanced additive system**

Provides excellent wear protection and enhances engine life without effecting emissions system life-time.

#### **Viscosity Control**

Delivers enhanced durability and lower oil consumption.

#### **Wide operating conditions**

Suitable for use in naturally aspirated and turbocharged petrol and light duty diesel engines in passenger cars and light commercial vehicles.

#### **Start-up Protect**

Excellent cold start properties and low temperature viscosity results in easy cold start whilst providing maximum cold start protection.

# PRODUCT INFORMATION



## Keeping the world moving since 1866™

Serving more than 100 countries around the globe, Valvoline is a leading marketer, distributor and producer of quality branded automotive and industrial products and services. Products include automotive lubricants including MaxLife™, the first motor oil specifically formulated for higher-mileage vehicles; transmission fluids; gear oils; hydraulic lubricants; automotive chemicals; specialty products; greases, and cooling system products.

For more information on Valvoline products, programs and services please visit [www.valvoline.com.au](http://www.valvoline.com.au) or contact the Technical Hotline on 1800 804 658 for product recommendations.

## Typical Properties

Typical property characteristics are based on current production. Whilst future production will conform to Valvoline™ specifications, variations in these characteristics may occur.

Valvoline Professional Series	Typical
SAE Viscosity Grade	10W-40
Viscosity @ 100 °C, mm <sup>2</sup> /s, ASTM D445	15.06
Viscosity @ 40 °C, mm <sup>2</sup> /s, ASTM D445	101.9
Viscosity Index, ASTM D2270	155
Density @ 15 °C, kg/L, ASTM D4052	0.8660
Total Base Number, mg KOH/g, ASTM D2896	9.8
CCS Viscosity, mPa.s @ -25 °C, ASTM D5293	<6700
Flash Point (COC), °C, ASTM D92	232
Pour Point, °C, ASTM D5950	-39

Note: Valvoline Professional Series SAE 10W-40 engine oil may be unsuitable for use in some engines, always consult owners' manual if in doubt.

This information only applies to products manufactured in the following location(s): Australia

Part Number	Pack Size
1279.20	20L
1279.28	208L
1279IBC	IBC
1279	Bulk

## Health and Safety

This product is not likely to present any significant health or safety hazards when used correctly in the right application. Safety Data Sheet (SDS) is available on request via your local sales office or 1800 804 658 or through our website [www.valvoline.com.au](http://www.valvoline.com.au)

## Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

## Storage

Storage We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60 °C, exposed to hot sun or freezing conditions.

## Author:

VP - Effective 30-06-2022  
Replaces - 1279/06